CENTRIFUGAL MONOBLOCK PUMP SERIES







TECHNICAL SPECIFICATIONS		
Max Total Head	38 Meters	
Max Flow Rate	1080 LPM	
Power Range	0.5HP to 3.0HP	
Type of Protection	IP - 44	
Insulation	F	

MATERIAL OF CONSTRUCTION		
Delivery Casing	Cast Iron FG 200	
Impeller	Cast Iron FG 200	
Motor Body	Cast Iron FG 200/Powder Coated Aluminium Extruded	
Shaft	EN8	

SALIENT FEATURES



Fitted with Thermal Over Load Protector



Cast Iron Motor Body



Optimised Electrical Design



Branded Mechanical Seal

APPLICATIONS

- Individual Houses
- Hospitals
- Hotels

- Domestic water supply
- Apartments
- Small Farms

- Industries
- Sprinkler Applications
- Agricultural

SELF PRIMING REGENERATIVE PUMP SERIES











TECHNICAL SPECIFICATIONS		
Voltage Range	Single Phase 140-260#V	
Max Total Head	63 Meters	
Max Flow Rate	4100 LPH	
Power Range	0.5HP to 1.5HP	
Insulation	F	
Type of Protection	IP-44	

- Varies with models. Kindly contact our Representatives

MATERIAL OF CONSTRUCTION		
Delivery Casing	Cast Iron FG 200	
Impeller	Forged Brass	
Motor Body	Aluminium Extruded/Die Cast /Cast Iron	
Shaft	EN8	

SALIENT FEATURES



High Quality Aluminium Motor Body



Double Shielded Ball Bearing



Suction Lift upto 6Mtrs



Branded Mechanical Seal

APPLICATIONS

- Booster Applications
- Car Washing
- Solar heating systems
- Near River belt
- Civil Constructions
- Gardening
- Hotels
- Garages
- Apartments in Metro cities
- Hospitals
- Industries
- Domestic / Household